



Ribbon fibre splicer


TYPE-72M12



Useful cloud hosted splicer services via your smartphone App.




Industry only dual independent ovens and Auto Clamping Adjustment System "Active-ACAS"



Dual independent ovens for productivity



Reduce your work time
Splicing 11s
Heating 35s



Active ACAS optimises splice loss
0.05dB



Touch optimised user interface and high resolution display

Specifications

Items	TYPE-72M12	
Optical fibre requirements	Material	Silica glass
	Profile types	Single/ SMF(G652), MMF(G651), DSF(G653), NZDSF(G655), BIF(G657)
	Fibre count	1, 2, 4, 5, 6, 8, 10, 12
	Cladding diameter	125µm
	Coating diameter	Single fibre coating dia: 200µm, 250µm, 500µm, 900µm Ribbon fibre thickness: 200-400µm
Standard performance	Applicable cable	Drop cable(2.0mm×3.1,or2.6mm), Indoor cable(2.0mm×1.6mm)
	Cleave length	10mm
	Splice loss (typical) *1	SMF 0.05dB, MMF 0.02dB, DSF 0.08dB, NZDSF 0.08dB
	Splice time (typical)	11sec (SM 12c Quick Mode), 14 sec (SM 12c Std. Mode)
	Heating time (typical)	35sec (FPS-6 sleeves, 40mm 1-12c Quick Mode)
	Splice & heat cycles per battery full charge *2	Approx 180
	Fibre view and magnification	2 CMOS cameras observation, 23X (zoom 46X)
	Proof test	1.96-2.09 N
	Applicable protection sleeve	60mm, 40mm & Sumitomo Electric nano sleeves
	Programs	Splice programs
Heating programs		Max 100
Functions	Splice image capture / Splice data storage	200 images / 10,000 splice data (internal memory only) 50,200 images / 20,000 splice data (with 16GB SD card)
	Automatic fibre count detection	Provided
	Automatic arc calibration	Automatically compensates for environmental condition changes
	Auto clamping adjustment system	Provided
	Reversible fibre holder system	Provided
	Dual automatic independent heaters	Provided
	User-selectable heater clamp operation	Provided
	Display of remaining Splice & Heat cycles	Provided (Battery mode)
	Onboard user training video	Provided
	Wireless LAN connectivity (Option) *3	Provided
Size / Weight	Size	128 (W) x 154 (D) x 130 (H) mm (without anti-shock rubber)
	Weight	1.8kg(without Battery) / 2.1kg(with Battery BU-16)
	Monitor	5.0" touch screen color LCD display
Terminals	DC output	DC 12V (for JR-6+)
	USB port	USB2.0 (mini-B type)
	Storage media	SD/SDHC memory card MAX32GB
Power supply	AC input	AC 100-240V, 50/60Hz (ADC-16)
	DC input	DC 10-15V, 7.5A
	Battery pack	Li-ion 10.8V, 6400mAh (BU-16)
Operating condition	Altitude : 0-3,660m, Temperature : -10-50°C, Humidity : 0-95%(non-condensing), Wind velocity : up to 15m/sec	
Storage condition	Temperature : -40-80°C, Humidity : 0-95%, Battery : -20-30°C(long term)	
Electrode life *4	1,500 arc discharges	
Software updates	Internet	
Data management	Can be stored, edited and analyzed by dedicated PC software	

*1 : Average value of the final inspection in room temperature with Sumitomo Electric identical fibre. Measured by cut-back method relevant to ITU-T and IEC standards.

*2 : Splice & Heat cycles may vary depending on the battery status and the operating environment.

*3 : Wireless LAN connectivity is not available in all countries. For more details, please refer to our Web site. <http://global-sei.com/sumitomo-electric-splicers/>

*4 : Achieved in lab condition. Electrode life may vary depending on the operating environment.

Environmental Durability*

	Test details
Shock resistance	Drop from 76cm on 5 faces (excluding top face)
Impact resistance	Equivalent to IK07 on LCD monitor
Water resistance	Equivalent to IPx2
Dust resistance	Equivalent to IP5x

*Splicer operation after shock, impact, water or dust tests, was confirmed under battery power, by Sumitomo Electric.
Does not guarantee the product will not be damaged by these conditions.

Basic Accessories

Part name	Part No.	Qty.
AC adapter	ADC-16 series	1 pc
AC power cord	PC-AC<X>*	1 pc
Cooling tray	—	1 pc
Spare electrode	ER-10	1 pair
Quick reference guide	—	1 pc
Carrying case with worktable	CC-72	1 pc
Hand strap	—	1 pc
USB cable	—	1 pc

*X=2(USA), 3(EU), 4(JP), 5(UK), 6(AUS), 7(South Africa)

Items listed in Basic Accessories are always included with the splicer body. Overall kit content may vary regionally. Please check with your local authorised reseller to confirm kit content in your region.

Accessories

	Part name	Part No.	Remarks	
Accessories for Splicer	SumiCloud card	WLSO series	For SumiCloud™ connection	
	Fibre holder	FHS-025		For 0.25 mm single fibre
		FHS-09		For 0.9 mm single fibre
		FHD-1		For drop and indoor cables (single fibre)
		FHC-3		For 3 mm cable
		FHM-2		For 2-fibre ribbon
		FHM-4		For 4-fibre ribbon
		FHM-5		For 5-fibre ribbon
		FHM-6		For 6-fibre ribbon
		FHM-8		For 8-fibre ribbon
		FHM-10		For 10-fibre ribbon
		FHM-12		For 12-fibre ribbon
		PCH-12A		200µm to 250µm pitch changing holder for pliable fibre ribbon
Lynx2-UML-S		For φ3 mm cord and φ0.9 mm single fibre		
Battery pack	BU-16	Li-ion 6,400mAh		
Battery charger	BC-16	—		
Car battery cable	PCV-16	For car battery operation (cigarette socket type)		
Electrodes	ER-10	—		
V-groove cleaning jig	VGT-2	Brush for cleaning V-groove		
Accessories	Handheld fibre cleaver	FC-8R-FC FC-8R-F	Automatic blade rotation cleaver with cleave counter Automatic blade rotation cleaver	
	Fibre cleaver	FC-6M-C	Table-top high precision cleaver	
		FC-6RM-C	Automatic blade rotation cleaver	
	Fiber Arrangement tool	OFA-01	Glue free fiber arrangement tool	
	Jacket remover	JR-MO3	Jacket remover for single fibre	
		JR-6+	Hot jacket remover for ribbon fibre	
	Fibre protection sleeve	FPS-1	60 mm sleeve for single fibre	
		FPS-40	40 mm sleeve for single fibre	
		FPS-5	40 mm sleeve for single fibre and up to 8-fibre ribbon	
		FPS-6	40 mm sleeve for single fibre and up to 12-fibre ribbon	
		FPS-D60	60 mm sleeve for single-fibre drop, and indoor cables	
Alcohol dispenser	HR-3	—		



Carrying case with worktable
CC-72



Handy cleaver
FC-8R series



Table-top cleaver
FC-6 / FC-6R series



Hot jacket remover
JR-6+



Pitch changing holder
PCH-12A



Available for
Lynx-Custom Fit™
Splice-On Connector

Sumitomo Electric Industries, Ltd.